

## 60 SERIES

## ECOTEX

### Product description

**60 SERIES** is a PVC free plastisol developed for textile printing by screen printing process. It has good adhesion on any sort of fabric, providing a solid, flexible and well defined image. Its washing performance is perfect. Its high covering power is another feature to take into account. It permits overprinting. Contrary to many competition pvc free plastisol, it shows high stability with time.

#### Recommended applications:

Virtually, almost any sort of fabric.

#### Finish:

Gloss.

#### Presentation:

Only viscosity needs to be adjusted, depending on the job, factory temperature and impression speed.

#### Limitations:

It has not enough resistance for certain sort of greases.

#### Other observations:

**61 SERIES**, with the similar properties to **60 SERIES**, gives 3D finishes if it is passed through the oven at temperatures of about 180°C.

#### Colors



#### Diluents:

Dilute with **Plastisol 60.DIL.** diluent.

#### Screens:

Emulsion with **ARGAZOL-E** (easy decoating) or **ARGAZOL-UV** (high performance and definition) with meshes from 29 to 130 meshes/cm.

#### Drying:

Approximately one minute in tunnel at 175°C, although this time can change depending on the colour and the ink deposited. It permits pre-curing with flash driers.

#### Security:

Carefully read the label directions and the tab Security of this ink.

These ink range fulfils the requirements of **OEKO-TEX 100 norm.**