

## 62 SERIES

## PLASTITEX

### Product description

**62 SERIES** is a plastisol developed for textile printing by screen printing process. It has good adhesion on any sort of fabric, providing a solid, flexible and well defined image. Its washing performance is perfect. Its high covering power is another feature to take into account. It permits overprinting.

#### Recommended applications:

Virtually, almost any sort of fabric.

#### Finish:

Gloss.

#### Presentation:

Only viscosity needs to be adjusted, depending on the job, factory temperature and impression speed.

#### Limitations:

It has not enough resistance for certain sort of greases.

#### Other observations:

**63 SERIES**, with the same properties than **62 SERIES**, gives 3D finishes if it is passed through the oven at temperatures of about 180°C.

#### Colors



001 002 006 009 052 105 110 111 207 222 225 245 305 405 420 425 435 500 515 605 615 665 675 715 815 825 900

#### Diluents:

Dilute with **Plastisol 62.DIL.** diluent.

#### Screens:

Emulsion with **ARGAZOL-E** (easy decoating) or **ARGAZOL-UV** (high performance and definition) with meshes from 29 to 130 meshes/cm.

#### Drying:

Approximately one minute in tunnel at 175°C, although this time can change depending on the colour and the ink deposited. It permits pre-curing with flash driers.

#### Security:

Carefully read the label directions and the tab Security of this ink.