

63 SERIES

SUBLITEX

Product description

63 SERIES is a plastisol developed for textile printing by screen printing process. It has good adhesion on any sort of fabric, providing a solid, flexible and well defined image. Its washing performance is perfect. Its high covering power is another feature to take into account. It permits overprinting.

Recommended applications:

Polyester. It also works on some products.
With some mix.

Finish:

Matt.

Presentation:

It is presented at printing viscosity, although sometimes, depending on the work, temperature workshop, print speed and the type of screen must be diluted with the suitable diluent or thickened with 66.ESP.

Other observations:

The transfer must be done in plates perfectly balanced and with conditions of reproducible work. Necessary test before production industrial.

Colors



Diluents:

Dilute with water to obtain viscosity desired. There is retardant.

Screens:

Use with AGUADIEL emulsion with fabrics
36-77 threads

Drying:

Air dry in about 10-15 minutes. In a 3-body air tunnel at 45 ° C it can be stacked.

Security:

Carefully read the label directions and the tab
Security of this ink.

07/2019

The information supplied is a result of our updated knowledge; it is supplied with good intention but under no circumstances it can be taken as a guarantee. Moreover, taking into account the great diversity of printable materials, the diversity of machinery and procedures to carry out the jobs, it is the user's responsibility to check the suitability of our products to obtain the objectives he desires, with the resources and procedures he has. The user must also make sure he complies with the current legislation, situation of patents and third party rights when applicable.