

## 99 SERIES

## MULTICURE UV

### Product Description

U.V. curable ink to be applied by screen printing, specially designed to be applied on polypropylene sheets and cellular polypropylene, as well as many other plastics including PVC, polystyrene, PC, ABS, acrylics... The formed film combines exceptional adherence with a high degree of flexibility, that permits chinking and die cutting. **99 SERIES** has high gloss, good surface finish and unbeatable adherence on those materials

#### Recommended applications:

Almost all plastics.

#### Drying:

Under 80 W lamp, it passes the talc test at speeds between 15-18 m/min.

#### Finish:

Gloss

#### Screens:

Use with **ARGAZOL-E** or **ARGAZOL-UV** with meshes from 150 to 165 meshes/cm.

#### Presentation:

It is presented ready to use with stencils from 150-165 meshes/cm at 20°C.

#### Security:

Carefully read the label directions and safety profile of this ink.

### Colores



Any other color can be prepared on request

11/2015

The information provided corresponds to our knowledge today; It is given in good faith but without guarantee. In addition, taking into account the wide variety of materials to print, the various equipment and procedures to realize it is your responsibility to check the validity of our products to achieve the goals that he intends, with the means and procedures he has. Similarly, the user must ensure compliance with current regulations, patent situation and rights of third parties where appropriate.